

Crimperroller



NEWS!

The new crop roller from Lyckegård

Crimperroller crushes green manure crops and processes the soil surface according to your needs.

Chevron-patterned blades on the drum cut and crush the plant and interrupts its growth. The cover crop mulch competes well with weeds and improves soil structure, nutrient content and conserves moisture in the soil surface. The drum can be filled with water for extra weight.



Suitable for all types of green manure, cover crops and stubble



The cover crop mulch is quickly degrading, improving nutrient, soil carbon content and soil structure



Can be used with a cultivator or a direct drilling machine in one passage



The cover crop mulch competes well with weeds and maintains soil moisture



Economic and environmentally friendly



Enables high capacity



Together with European farmers, Lyckegård has developed the concept of Crimperoller + Kvikffinn

The concept involves processing of cover crops and mechanical weed control in one passage before sowing. We present two alternatives to add to your crop rotation. Timing and method depend on the presence of perennial weeds.

-Alternative 1:

Processing of a cover crop prior to sowing a spring or fall crop with a front mounted Crimperoller and a rear mounted Kvikffinn. The combination finishes the cover crop and plant residues are left on the surface. After that, sowing can be carried out with a disc seeder, with high pressure on the discs.

-Alternative 2:

Summer tread, green manure and fall crop sowing. An effective short summer tread can be managed with 3-4 crossings with Kvikffinn with a 2-3 weeks interval to fight weeds. A fast growing green manure crop is sown and after 2-3 months a fall crop can be established with a Crimperoller together with a direct drill. The green manure crop contributes with nutrition, retains soil moisture and protection against weeds.

Technical data

Models:	3000 / 4000 / 4500
Working width:	3m / 4m / 4,5m
Transport width:	2,99m
Transport mode:	4000 and 4500 are foldable for transport
Diameter of drum:	400 mm
Outer diameter:	600 mm
Weight:	990 kg/ 1750 kg/ 1950 kg
Water filling:	300 kg
Equipment:	Lights, hazard plates, bolted blades, blades with sharp and blunt edges.




lyckegård

Lyckegård Group AB

Trollebergsvägen 102-28
245 61 Staffanstorp, Sweden

+46 455 34 48 90
info@lyckegard.com

lyckegard.com

